



EVO Green

Thermal Receipt Printer

The EVO Green Thermal Receipt Printer is our most efficient receipt printer. Engineered to operate day-in and day-out in the harshest of environments, the EVO Green provides the steadfast performance you need while using a fraction of the energy. Perfect for high volume retail and hospitality operations, the EVO Green features quick receipt printing, JamFree Autocutter Technology, and is backed by the best warranty in the industry.




receipt printer

Key Features

- Energy Star certified
- Power supply and interface cable(s) included
- Drop-in easy thermal paper loading
- JamFree AutoCutter technology
- ESC/POS and OPOS compatible
- Wall-mountable
- 3-Year Warranty includes 2-Day Advance Exchange Service

EVO Green Thermal Receipt Printer Specifications

PART NUMBER	EVO-PT3-2GUS	EVO-PT3-2GUSE
SPECIFICATIONS		
Interfaces	USB/Serial	USB/Serial/Ethernet
Interface Details	USB 2.0/RS-232C	USB 2.0/ RS-232C /(10/100)
Emulation	ESC/POS Command Compatible	
Print Method	Direct Thermal	
Printing Speed	7.87"/sec (200 mm/sec)	
Dot Density	180 DPI x 180 DPI	
Printing Direction	Unidirectional with Friction Feed	
Sensors	Cover Open, Paper Low, Paper End	
CASH DRAWER PORTS	2 Circuits (24 V, 1 A max)	
RELIABILITY	TPH Life 99.42 miles MCBF 60,000,000 Lines	
PAPER		
Type	Thermal Paper	
Width	1.9" (50 mm) - 3.15" (80 mm)	
Thickness	0.002" (0.06 mm) - 0.0035" (0.09 mm)	
Roll Diameter	Max 3.15" (80 mm)	
Roll Core Inner Diameter	0.492" (12.5 mm) ± 0.019" (0.5 mm)	
CHARACTER SET	Alpha Numeric Character 95 Extended Graphics 128 x 18 page (1 space per page) International Characters 14	
CHARACTER/LINE	Font A (12 x24) 42 columns	Font B (9 x17) 56 columns
BARCODES SUPPORTED	EAN-8, EAN-13, CODE 39, ITF, UPC-A, CODABAR, CODE 93, CODE 128, PDF 417(2D)	
AUTO CUTTER		
Type	JamFree auto-retracting guillotine	
Life	1,500,000 Cuts	
Cutting Method	Full/Partial Cut	
PHYSICAL		
Dimension	6.1"(W) x 8"(D) x 6.1"(H)	
Weight	3.7 lbs	
Color	Black	
ELECTRICAL	100–240 VAC 50/60 Hz (input)	24 VDC/1.5 A (output)
ENVIRONMENTAL		
Temperature	41°F to 104°F operating -4°F to 140°F storage	
Humidity	35%–80% non condensing (operation)	10%–90% non condensing (storage)
WARRANTY	3-Year includes 2-Day Advance Exchange Warranty Service, 2-Year on Autocutter and Print Head	
CERTIFICATIONS	FCC, UL, CE, Energy Star	
OPERATING SYSTEM	WIN 95/WIN 98/WIN 2000/WIN XP/VISTA/Win 7/Win 8/OPOS drivers available	



ACCESSORIES

ZWE-CRW	2-Year Warranty Extension
ZOE-CRW3	3-Year Overnight Exchange
ZOE-CRW5	5-Year Overnight Exchange