

## ION

## Fit POS Terminal

The ION Fit is part of the cost-effective, high performance POS-X ION Series. A sleek design available with an Intel® Atom™ Dual-Core or Celeron™ Quad-Core processor, combined with a solid fanless construction make the ION Fit a quality POS terminal. Powerful, yet energy-efficient, the ION Fit is the perfect choice for any application requiring a dependable and affordable solution.



### Key Features



#### Processors

Available with Quad-Core Celeron J1900 or Atom Dual-Core D2550 1.86GHz processors



#### Touchscreen

15" (381mm) 5-wire resistive touch display or 15" Zero-Bezel touchscreen technology



#### Hard Drive

2.5" (64mm) 320GB HDD or 60-120GB SSD



#### Built In Cable Management

Keeps cords out of sight



#### Fanless

Ideal for dusty or dirty environments



#### Energy Efficient

Conserving natural resources, energy and minimizing waste



#### Optional Accessories

Integrated MSR, LCM customer display, 8.4" (213mm) rear LCD, 15" (381mm) rear LCD display, or Biometric reader.

### ■ POS-X Warranty

#### Industry-leading Warranty Protection

- 3 year warranty
- \*2-day Advance Exchange - standard on all products
- \*Warranty extensions and overnight exchanges are available to provide means to further reduce the total cost of ownership

\*Available in USA and Canada

### ■ POS-X Service and Support

#### 24/7 Technical Support and Lifetime Customer Support

- 24/7 access to our USA-based experienced technical support representatives
- Support techs utilize advanced techniques such as remote access for quick and accurate system analysis
- Lifetime support on all POS-X products

MODELS	ION-TP3A-F	ION-TP3C-F	ION-TP3A-D
Processor	Intel Celeron J1900 2.42GHz Quad-Core		Intel Atom D2550 1.86 GHz Dual Core
Bezel	Standard Bezel	TruFlat Bezel	Standard Bezel
Chip Set	Processor Integrated		CPU integrated graphic + NM10, 2W
System Memory	1 x DDR3 SO-DIMM 4-8GB		1 x DDR3 SO-DIMM 2-4GB
Hard Drive	320GB HDD or 60-120GB SSD		
Graphic Memory	Intel Gen7 at 300MHz		DX9, Graphic core speed at 640MHz
Electrical	65W/19V		
PORTS			
USB	6 x USB Type A (USB 3.0 / 2.0 x1, USB 2.0 x5)		4 x USB Type A (default) (USB 2.0)
Serial	3 x RJ45 COM4 with 5V/12V		4 x RJ45 COM4 with 5V/12V
VGA			1
GigaLAN (10/100/1000)			1 x RJ45
PHYSICAL			
Housing	ABS		
Weight	12.27lb (5.57kg)		
Dimensions (w/base) (WxDxH)	14.3" x 8.26" x 14.56" (364mm x 210mm x 370mm)		
Tilt Angle	40° ~ 90°		
Housing Color	Black		
LCD Display	15" (381mm) LED LCD		
Resistive Touch	5-Wire Resistive		
ENVIRONMENTAL			
Operating Temperature	32°F to 95°F (0°C to 35°C)		
Humidity	20% ~ 85% non condensing		
Warranty	3-year warranty with free *2-day Advance Exchange Service		
Certifications	FCC, CE, LVD, RoHs, NOM		
Supported OS	POS Ready7, Win 7 Pro/ Available with no O/S		
OPTIONAL ACCESSORIES			
ION-MR3	3-track Magnetic Stripe Reader with USB interface		
ION-RD3-LCM	Integrated 2 x 20 LCM customer display		
ION-RD3-LCD8	Integrated rear display, 8.4" (213mm) LCD, VGA		
ION-RD3-LCD15A	Integrated 15" (381mm) Bezeled Rear LCD, for ION TP3 & TM3		
ION-RD3-LCD15C	Integrated 15" (381mm) TruFlat Rear LCD, for ION TP3 & TM3		
ION-BR3	ION Integrated BIO Reader for ION TP3 & TM3		
WARRANTY EXTENSION AND UPGRADES			
ZWE-TPC	2-Year Warranty Extension		
ZOE-TPC3	*3-Year Overnight Exchange		
ZOE-TPC5	*5-Year Overnight Exchange		

\*Available in USA and Canada



1975 Midway Lane, Suite O  
 Bellingham, WA 98226  
 sales@pos-x.com  
 360.738.8433  
 www.pos-x.com

